

# SOLID DISSOLVERS SINGLE PRODUCT

The 595 single solid dissolver provides diluted solution of one solid product held in an integrated reservoir, ready for on demand pumping when indicated by the system controller.

## Features

- ▲ No electricity required
- ▲ Runs off line water pressure (30-90 psi)
- ▲ Uses low cost, reliable float technology
- ▲ Includes adjustable pressure gauge and removable filter
- ▲ Atmospheric siphon breaker included for backflow protection
- ▲ Translucent body allows viewing of water level in reservoir
- ▲ Takes advantage of the reduced transportation and storage costs, and worker safety benefits of solid chemistry



## System Advantages

### USES RELIABLE, TIME-PROVEN FLOAT TECHNOLOGY

No electric solenoids to burn out, no transformers to fail when current spikes. The dissolver's float technology has been proven in the car wash industry for over 40 years. And there are no reed switches to gum up and stick. The result: consistent, reliable performance, reduced down time, and reduced service calls.

### EASY TO INSTALL

Attach the unit using 4 bolts, hook the float to the valve, attach the water inlet and the solution discharge tubing—that's it. The unit is ready to go to work.

### DESIGNED FOR CHEMICAL RESISTANCE

Molded parts are made of polypropylene and polyethylene; metal parts are made of Hastelloy for maximum chemical resistance.

### SPECIALIZED NOZZLE TECHNOLOGY

Spray nozzles are molded polypropylene to avoid chemical attack. Four spray patterns are available to ensure optimum dissolve rates.

## Model Information

<u>Model</u>	<u>Description</u>
595	Single product solid dissolver, float-activated, with integrated reservoir
Dimensions:	15"W x 28"H x 10"D
Weight:	25 pounds (with water)

